



# HYDRO<sup>TM</sup> PNEU

Pressure Tank



**FIXED DIAPHRAGM TYPE**


**HPFD 24/10**
**HPFDH 24/10**
**HPFD 60/10**
**HPFD 100/10**

Model	Vol (Ltrs)	Dia (mm)	Height (mm)	Connection (Inch)	Max Working Pressure (Bar)	Weight (Kgs)
HPFD 24	24	290	440	1"	10	5.6
HPFDH 24	24	290	447	1"	10	5.9
HPFD 60	60	387	623	1"	10	12.4
HPFD 100	100	428	810	1"	10	17.1

### Product Features

- Fixed diaphragm (Butyl Rubber) tank designs
- Reinforced stainless steel water connection
- O-ring protected leak free air valve cap
- Durable & highly adhesive powder coating finish
- Suitable for a wide range of applications
- Extensively tested maintenance free tanks
- Fully made of food-grade and NSF/FDA approved raw materials

### Applications

- Booster Systems
- HYPN Systems
- Boiler Systems
- Thermal Expansion
- Irrigation Systems

Imported & Marketed By -



Products & Services Pvt. Ltd.

### AQUA Products & Services Pvt Ltd

Shed No 13, S.No. 78/1, Baba Khan Industrial Estate,  
Shivne, Pune, Maharashtra, 411023, India.

Mobile : +91 9049988059

Email : enquiry@aquaproducts.in

Website : www.aquaproducts.in / hydro-pneu.in



www.aquaproducts.in



www.hydro-pneu.in